

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.

0.9

9.4 MAX.

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

CONTACT: COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

WITHSTANDING VOLTAGE: 1000V AC rms

CURRENT RATING: 3A PER CONTACT CONTACT RESISTANCE: 25mΩ MAX. INSULATOR RESISTANCE: 5000MΩ min.

SHELL: STEEL, NICKEL PLATED



ISSUE NUMBER
ORIGINAL
(1)

EDAC INC TORONTO, ONTARIO CANADA N TO QUALITY & SERVICE

638 SERIES D-SUB CONNECTOR

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NOTES:

MATERIAL:

DIELECTRIC

SW REFERENCE NO.: 628 A	SSEMBLY	
DRAWN: C.B	DATE: AUG. 01/2018	
CHECKED:	DATE:	
SCALE: 1:1	SHEET 1 OF 1	
DRAWING NUMBER: 638-044-2	231-079 ISSUE	
PART NUMBER: 638-044-2	231-079 1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

	EI TORON C	
YOUR CONNECTION TO	QUALIT	