
TOLERANCE UNLESS OTHERWISE SPECIFIED .X ±0.25 .XX ±0.13 .XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.




ISSUE NUMBER ORIGINAL (1)



50 ±0.10

4



NOTES:

MATERIAL:	SPCC, T=0.35mm
SHELL:	NICKEL PLATED 50µ" MIN. OVERALL
SHELL PLATING:	COPPY ALLOY
TERMINAL:	GOLD FLASH PLATING ON CONTACT AREA,
TERMINAL PLATING:	TIN PLATED ON SOLDER TAIL, 50µ" MIN,
	NICKEL UNDERPLATED OVERALL
HOUSING:	WHITE PBT


ELETRICAL: **RATED VOLTAGE:** 30 Vrms MAX. **RATED CURRENT:** 1.5A **INSULATION RESISTANCE:** 1000Ω MIN. 500V DC DIELECTIV WITHSTANDING VOLTAGE: 500V AC CONTACT RESISTANCE: 30mΩ **ENVIROMENTAL:** -40°C TO +80°C **OPERATING TEMPERATURE:** STORAGE STORAGE TEMPERATURE: -20°C TO +60°C STORAGE LIFE: 12 MONTHS MAX.

MECHANICAL: INSERTION FORCE: EXTRACTION FOCE: DURABILITY:

35N MAX

10N MIN. 1500 CYCLE

		ACAD REFERENCE NO.: 691C104-X90-12X			
	CABLE END SOLDER CUP		DRAWN: C.B	DATE: December 1	5, 2020
			CHECKED:	DATE:	
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: 2:1	SHEET 1 OF	1
	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 69	IC104-X90-12X	ISSUE
	YOUR CONNECTION TO QUALITY & SERVICE	MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER: 69	1C104-290-120	1



8 8 8 8

COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

	EDAC INC TORONTO, ONTARIO		
	CANADA		
YOUR CONNECTION TO QUALITY & SERVICE			