



NOTES:

## 1. MATERIALS: INSULATOR: CONTACT:

2. VOLTAGE RATING:

3. CURRENT RATING:

4. CONTACT RESISTANCE:

PBT, BLACK, UL 94V-0 PHOSPHOR BRONZE, SELECT 30μ" GOLD PLATING ON CONTACT AREA TIN ON TAILS OVER NICKEL 125 VAC RMS 1.5 AMPS @25°C 20mΩ MAX 5. DIELECTRIC WITHSTANDING: 1000V AC CONTACT TO CONTACT OR 1500VDC CONTACT TO SCREEN AND TEST PANEL @0.5mA 50Hz OR 60Hz 60s
6. DURABILITY: 750 CYCLES MIN
7. MATING/UNMATING FORCE: 30N/3.06KG MAX
8. RETENTION STRENGTH: 30N MIN FOR 60s ±5s
9. OPERATING TEMP: -40°C TO +85°C
10. STORAGE TEMP: -40°C TO +85°C RELATIVE HUMIDITY <80%</li>

## MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

	RJ45, 2 PORTS, RIGHT ANGLE PCB MOUNT		ACAD REFERENCE NO .: J96 Assembly		
			DRAWN: C.B	DATE: January 20	, 2020
			CHECKED:	DATE:	
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: 2:1	SHEET 2 OF	2
	YOUR CONNECTION TO QUALITY & SERVICE	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: J96 Assembly		ISSUE
			PART NUMBER: J9602886	62P35121	1

THIS IS A C.A.D. GENERATED DRAWING

DO NOT MAKE MANUAL REVISIONS TO MASTER.

TOLERANCE UNLESS OTHERWISE SPECIFIED

> .X ±0.25 .XX ±0.13

.XXX ±0.05



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

	MATES WITH MO

ISSUE NUMBER

(1)

