



THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.





ORIGINAL

(1)

## NOTES:

1. MATERIALS: **INSULATOR:** 

2. VOLTAGE RATING:

CONTACT:

PBT, BLACK, UL 94V-0 PHOSPHOR BRONZE, SELECT 30µ" GOLD PLATING ON CONTACT AREA TIN ON TAILS OVER NICKEL 125 VAC RMS 1.5 AMPS @25°C

- 3. CURRENT RATING:
- 4. CONTACT RESISTANCE:

 $20m\Omega MAX$ 

	1500VDC CONTACT TO SCREEN AND TEST PANEL
	@0.5mA 50Hz OR 60Hz 60s
6. DURABILITY:	750 CYCLES MIN
7. MATING/UNMATING FORCE:	30N/3.06KG MAX
8. RETENTION STRENGTH:	30N MIN FOR 60s ±5s
9. OPERATING TEMP:	-40°C TO +85°C
10. STORAGE TEMP:	-40°C TO +85°C RELATIVE HUMIDITY <80%

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

5. DIELECTRIC WITHSTANDING: 1000V AC CONTACT TO CONTACT OR

	RJ45, 4 PORTS, RIGHT ANGLE PCB MOUNT		ACAD REFERENCE NO.: J96 Assembly		
			DRAWN: C.B	DATE: January 20	, 2020
			CHECKED:	DATE:	
	EDAC INC TORONTO, ONTARIO CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 2:1	SHEET 2 OF	2
			DRAWING NUMBER: J96 Assembly		ISSUE
	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: J9604886	62P35221	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.