



## NOTES:

1. MATERIALS: INSULATOR: CONTACT:

2. VOLTAGE RATING:

3. CURRENT RATING:

4. CONTACT RESISTANCE:

PBT, BLACK, UL 94V-0 PHOSPHOR BRONZE, SELECT 30μ" GOLD PLATING ON CONTACT AREA TIN ON TAILS OVER NICKEL 125 VAC RMS 1.5 AMPS @25°C 20mΩ MAX 5. DIELECTRIC WITHSTANDING:1000V AC CONTACT TO CONTACT OR<br/>1500VDC CONTACT TO SCREEN AND TEST PANEL<br/>@0.5mA 50Hz OR 60Hz 60s6. DURABILITY:750 CYCLES MIN7. MATING/UNMATING FORCE:30N/3.06KG MAX8. RETENTION STRENGTH:30N MIN FOR 60s ±5s9. OPERATING TEMP:-40 °C TO +85 °C10. STORAGE TEMP:-40 °C TO +85 °C RELATIVE HUMIDITY <80%</td>

## MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

	RJ45, 6 PORTS, RIGHT ANGLE PCB MOUNT		ACAD REFERENCE NO .: J96 Assembly		
			DRAWN: C.B	DATE: January 20	, 2020
			CHECKED:	DATE:	
	EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 2:1	SHEET 2 OF	2
			DRAWING NUMBER: J96 Assembly		ISSUE
			PART NUMBER: J9606886	62P00221	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.