



INSULATOR:	PBT, BLACK, UL 94V-0
CONTACT:	PHOSPHOR BRONZE,
	SELECT 30µ" GOLD PLATING ON CONTACT AREA
	TIN ON TAILS OVER NICKEL
2. VOLTAGE RATING:	125 VAC RMS
3. CURRENT RATING:	1.5 AMPS @25°C

4. CONTACT RESISTANCE:

 $20m\Omega MAX$

	1500VDC CONTACT TO SCREEN AND TEST PANEL
	@0.5mA 50Hz OR 60Hz 60s
6. DURABILITY:	750 CYCLES MIN
7. MATING/UNMATING FORCE:	30N/3.06KG MAX
8. RETENTION STRENGTH:	30N MIN FOR 60s ±5s
9. OPERATING TEMP:	-40°C TO +85°C
10. STORAGE TEMP:	-40°C TO +85°C RELATIVE HUMIDITY <80%

(1)

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

	RJ45, 6 PORTS, RIGHT ANGLE PCB MOUNT		ACAD REFERENCE NO.: J96 Assembly		
			DRAWN: C.B	DATE: January 20	, 2020
			CHECKED:	DATE:	
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: 2:1	SHEET 2 OF	2
	YOUR CONNECTION TO QUALITY & SERVICE	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: J96 Assembly		ISSUE
			PART NUMBER: J9606886	32P35221	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.